



### Gree Drywall Fiber Joint Tape

#### Product Description

GREE Drywall Fiber tapes are made using USA grade fiberglass mesh for stronger joints. Eliminates blisters & bubbles. Fast and easy application, no bedding coat needed. It has 33% thinner mesh for flatter and smooth finish.

#### Product Features & Application

- USA Grade Fiber Mesh.
- Joints and seams on walls and roofs.
- Suitable for drywall surfaces.
- Ideal for wall plastering application.

#### Product Properties

No	Testing Items		65g/m2
1	Yarn/Roving Spec. Tex	Warp Yarn	33 Tex
		Weft Roving	67 Tex
2	Breanking Strength	Warp Yarn	400 N
		Weft Roving	400 N
3	Cell Size	mm	Warp Yarn 3
			Weft Roving 3
4	Glue Tape		Adhesive Latex
5	Finished Mesh Weight (g/m2)		65±3g/m2
6	Raw Fabric (g/m2)		45±3g/m2
7	Mesh Size		8 X 8/inch
8	Glue Content (%)		30%±3
9	Moisture Content (%)		≤0.5 %
10	Roll Width		50mm±0.2
11	Roll Length		90m±0.3

#### Application Technique

Clean the surface well with dry cloth. Ensure surface is free from grease, oil, stains and dust. For Better appearance mask outside joint areas with Gree Masking Tape before application. Cut nozzle to desired size and extrude sealants to joint areas with sealant applicator gun. Tool immediately after sealant application and remove the Gree tape before sealant cures.

