



# GREE

Quality You Can Trust

## TECHNICAL DATA SHEET

### Gree Nail Free Glue

#### R-918 Super strong Adhesive

##### Product Description

Gree Nail Free Glue is a one-part mild solvent and rubber-based all purpose construction adhesive that delivers a consistently strong and lasting bond on most building substrates.

##### Product Features & Application

- High strength
- Environmentally Friendly
- Eliminates the need of screws and nails (No Nail)
- Flexible
- Non-drip/non-sag formulation
- Easy to extrude even at low temperatures

##### Product Properties

- Appearance: Beige
- Consistency: Thixotropic
- Homogeneity: No seediness, no lumps
- Tack free time: 24°C-33°C:5 Mins-8 mins
- Setting Time: 5-6 hours (Depending on surface porosity)
- Full Cure: 2 days for porous substrate & 1 week for non-porous substrates
- Extrudability / ease in application: Easy to extrude

##### Area of Application

- Aluminum composite panel Sheets Cladding
- Raised Flooring
- Sheet Flooring or joints
- Cornices or Moldings
- Mirror
- Steel Stud/ Fiber Board
- Metal or aluminum door strip to floor or walk
- Ceramic, Tiles, and Glass
- Timber or fiber cement sheeting to cement block or brick walls
- In the groove of tongue and groove flooring
- EPS Foam
- Plastics

All technical information and data mentioned above are only test values from RATCs laboratory, they shall not be considered as specification standards or guarantee values. The user is responsible for determining whether Gree product is fit for specific purposes or applications by conducting suitability testing, before placing a purchase order.

